AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A curable resin composition, comprising:

a poly(arylene ether); wherein the poly(arylene ether) is a capped poly(arylene ether) produced by capping a poly(arylene ether) consisting essentially of the polymerization product of at least one monohydric phenol having the structure

$$R^{1}$$
 R^{2}
 R^{2}
 R^{3}
 R^{4}

wherein R¹-R⁴ are each independently hydrogen, halogen, primary or secondary C₁-C₁₂ alky₁, C₂-C₁₂ alky₁, C₂-C₁₂ alky₁, C₁-C₁₂ aminoalkyl, C₁-C₁₂ hydroxyalkyl, phenyl, C₁-C₁₂ haloalkyl, C₁-C₁₂ aminoalkyl, C₁-C₁₂ hydroxyalkyl, phenyl, halohydrocarbonoxy wherein at least two carbon atoms separate the halogen and oxygen atoms;

an acryloyl monomer; and

an allylic monomer;

wherein the curable resin composition is a powder.

- 2 (Canceled)
- 3 (Original) The curable resin composition of Claim 1, wherein the poly(arylene ether) has a free hydroxyl group content less than about 500 micrograms per gram.

- 4. (Canceled)
- 5. (Currently Amended) The curable resin composition of Claim [[4]] 1, wherein the capped poly(arylene ether) comprises a capping group having the structure

$$\begin{array}{c|c}
C & R^6 \\
\hline
C & R^8
\end{array}$$

wherein R^6 - R^8 are each independently selected from the group consisting of hydrogen, C_1 - C_{12} alkyl, C_2 - C_{12} alkenyl, C_6 - C_{18} aryl, C_7 - C_{18} mixed (alkyl-aryl), C_2 - C_{12} alkoxycarbonyl, C_7 - C_{18} aryloxycarbonyl, C_8 - C_{18} mixed (alkyl-aryl)oxycarbonyl, nitrile, formyl, carboxylate, imidate, and thiocarboxylate.

- 6 (Canceled)
- 7 (Original) The curable resin composition of Claim 1, wherein the poly(arylene ether) has an intrinsic viscosity of about 0.1 to about 0.5 deciliters/gram in chloroform at 25°C.
- 8 (Original) The curable resin composition of Claim 1, comprising about 10 to about 50 parts by weight of the poly(arylene ether) per 100 parts by weight resin.

9. (Original) The curable resin composition of Claim 1, wherein the acryloyl monomer comprises at least one acryloyl moiety having the structure

$$\begin{array}{c|c}
C & C & C \\
C & \xi_{16} & \xi_{17}
\end{array}$$

wherein R¹⁶ and R¹⁷ are each independently selected from the group consisting of hydrogen and C₁-C₁₂ alkyl, and wherein R¹⁶ and R¹⁷ may be disposed either cis or trans about the carbon-carbon double bond.

10. (Original) The curable resin composition of Claim 1, wherein the acryloyl monomer comprises at least one acryloyl moiety having the structure

wherein R¹⁸-R²⁰ are each independently selected from the group consisting of hydrogen, C₁-C₁₂ alkyl, C₂-C₁₂ alkenyl, C₆-C₁₈ aryl, C₇-C₁₈ mixed (alkyl-aryl), C₂-C₁₂ alkoxycarbonyl, C₇-C₁₈ aryloxycarbonyl, mixed C₈-C₁₈ (alkyl-aryl)oxycarbonyl, nitrile, formyl, carboxylate, imidate, and thiocarboxylate.

11. (Original) The curable resin composition of Claim 10, wherein the acryloyl monomer comprises at least two acryloyl moieties.

- 17. (Original) The curable resin composition of Claim 1, wherein the acryloyl monomer is selected from the group consisting of trimethylolpropane trimethacrylate, trimethylolpropane triacrylate, 1,6-hexanediol dimethacrylate, 1,6-hexanediol diacrylate, ethylene glycol diacrylate, propylene glycol dimethacrylate, propylene glycol diacrylate, cyclohexanedimethanol dimethacrylate, cyclohexanedimethanol diacrylate, butanediol dimethacrylate, butanediol diacrylate, diethylene glycol dimethacrylate, diethylene glycol diacrylate, triethylene glycol dimethacrylate, triethylene glycol dimethacrylate, isobornyl methacrylate, isobornyl acrylate, methyl methacrylate, methyl acrylate, and mixtures comprising at least one of the foregoing acryloyl monomers.
- 13. (Original) The curable resin composition of Claim 1, wherein the acryloyl monomer is selected from the group consisting of trimethylolpropane trimethacrylate, trimethylolpropane triacrylate, and combinations comprising at least one of the foregoing acryloyl monomers.
- 14. (Original) The curable resin composition of Claim 1, comprising about 5 to about 60 parts by weight of the acryloyl monomer per 100 parts by weight resin.

15. (Original) The curable resin composition of Claim 1, wherein the allylic monomer comprises an allylic moiety having the structure

wherein R²¹ is selected from the group consisting of hydrogen and C₁-C₆ alkyl.

- 16. (Original) The curable resin composition of Claim 15, wherein the allylic monomer comprises at least two allylic moieties.
- 17. (Original) The curable resin composition of Claim 1, wherein the allylic monomer is selected from the group consisting of allyl alcohol, methallyl alcohol, 2-ethyl-2-propen-1-ol, allyl formate, allyl acetate, allyl butyrate, allyl benzoate, methallyl acetate, allyl fatty esters, allyl methyl ether, allyl ethyl ether, allyl tert-butyl ether, allyl methylbenzyl ether, alkoxylated allylic alcohols, diallyl adipate, diallyl citraconate, diallyl diglycolate, diallyl ether, diallyl furnarate, diallyl isophthalate, diallyl itaconate, diallyl maleate, diallyl phthalate, diallyl terephthalate, triallyl aconitate, triallyl cyanurate, triallyl isocyanurate, triallyl phosphate, triallyl trimellitate, tetraallyl o-silicic acid, and mixtures comprising at least one of the foregoing allylic monomers.

- 13. (Original) The curable resin composition of Claim 1, wherein the allylic monomer is selected from the group consisting of diallyl adipate, diallyl citraconate, diallyl diglycolate, diallyl ether, diallyl furnarate, diallyl isophthalate, diallyl itaconate, diallyl maleate, diallyl phthalate, diallyl terephthalate, triallyl aconitate, triallyl cyanurate, triallyl isocyanurate, triallyl phosphate, triallyl trimellitate, tetraallyl o-silicic acid, and mixtures comprising at least one of the foregoing allylic monomers.
- 19. (Original) The curable resin composition of Claim 1, wherein the allylic monomer is diallyl phthalate.
- 20. (Original) The curable resin composition of Claim 1, wherein the allylic monomer is substantially free of polymerizable moieties other than allylic moieties.
- 2.. (Original) The curable resin composition of Claim 1, comprising about 20 to about 80 parts by weight of the allylic monomer per 100 parts by weight resin.
- 22. (Original) The curable resin composition of Claim 1, further comprising a curing catalyst.
- 23. (Original) The curable resin composition of Claim 22, wherein the curing catalyst is selected from the group consisting of benzoyl peroxide, dicumyl peroxide, methyl cthyl ketone peroxide, lauryl peroxide, cyclohexanone peroxide, t-butyl hydroperoxide, t-butyl benzene hydroperoxide, t-butyl peroctoate, 2,5-dimethylhexane-2.5-dihydroperoxide, 2.5-dimethyl-2.5-di(t-butylperoxy)-hex-3-yne, di-t-butylperoxide, tbutylcumyl peroxide, alpha, alpha'-bis(t-butylperoxy-m-isopropyl)benzene, 2,5-dimethyldi(t-butylperoxy 2,5-di(t-butylperoxy)hexane, dicumylperoxide, isophthalate, butylperoxybenzoate, 2,2-bis(t-butylperoxy)butane, 2,2-bis(t-butylperoxy)octane, 2,5dimethyl-2,5-di(benzoylperoxy)hexane, di(trimethylsilyl)peroxide, trimethylsilylphenyltriphenylsilyl peroxide, 2,3-dimethyl-2,3-diphenylbutane, trimethylsilyloxy-2,3-diphenylbutane, and mixtures comprising at least one of the foregoing curing catalysts.
- 24. (Original) The curable resin composition of Claim 22, comprising about 0.1 to about 10 parts by weight of the initiator per 100 parts by weight resin.

- 25. (Original) The curable resin composition of Claim 1, further comprising an additive selected from the group consisting of flame retardants, flame retardant synergists, mold release agents, lubricants, antioxidants, thermal stabilizers, ultraviolet stabilizers, pigments, dyes, colorants, anti-static agents, fibrous reinforcements, disc-shaped fillers, low-aspect ratio fillers, synthetic resins, natural resins, thermoplastic elastomers, and mixtures comprising at least one of the foregoing additives.
- 26. (Original) The curable resin composition of Claim 1, further comprising a filler.
- 27. (Original) The curable resin composition of Claim 26, comprising a filler selected from the group consisting of silica powder, fused silica, crystalline silica, natural silica sand, boron-nitride powder, boron-silicate powder, alumina, magnesium oxide, wollastonite, calcium sulfate, calcium carbonate, talc, glass spheres, kaolin, mica, feldspar, nepheline syenite, silicate spheres, flue dust, cenospheres, fillite, aluminos licate, quartz, quartzite, perlite, Tripoli, diatomaceous earth, silicon carbide, molybdenum sulfide, zinc sulfide, mullite, calcium silicate, zirconium silicate, barium titanate, barium ferrite, barium sulfate, aluminum, bronze, zinc, copper, nickel, carbon black, graphite, glass flakes, flaked silicon carbide, flaked aluminum diboride, aluminum flakes, steel flakes, wood flour, cellulose, cotton, sisal, jute, starch, cork flour, lignin, ground nut shells, corn, rice grain husks, polyester fibers, polyvinylalcohol fibers, aromatic polyamide fibers, polybenzimidazole fibers, polyimide fibers, polyphenylene sulfide fibers, polyether ether ketone fibers, boron fibers, silicon carbide fibers, mixed oxide fibers, silicon carbide fibers, alumina fibers, boron carbide fibers, iron fibers, nickel fibers, copper fibers, glass fibers, quartz, vapor-grown carbon fibers, combinations comprising at least one of the foregoing fillers, and combinations comprising at least one of the foregoing fillers and a surface-treating agent.

- 28. (Original) The curable resin composition of Claim 1, wherein the composition is substantially free of alkenyl aromatic monomers in which an alkenyl substituent is directly bonded to an aromatic ring.
- 29. (Original) The curable resin composition of Claim 1, wherein the powder is substantially free of particles having any dimension greater than about 300 micrometers.
- 30. (Original) The curable resin composition of Claim 1, having a melting temperature greater than about 50°C.

31. (Currently Amended) A curable resin composition, comprising:

about 10 to about 50 parts by weight of a poly(arylene ether); wherein the poly(arylene ether) is a capped poly(arylene ether) produced by capping a poly(arylene ether) consisting essentially of the polymerization product of at least one monohydric phenol having the structure

$$R^1$$
 R^2
 R^3
 R^4

wherein \mathbb{R}^1 - \mathbb{R}^4 are each independently hydrogen, halogen, primary or secondary C_1 - C_{12} alkyl, C_2 - C_{12} alkenyl, C_2 - C_{12} alkylyl, C_1 - C_{12} aminoalkyl, C_1 - C_{12} hydroxyalkyl, phenyl, C_1 - C_{12} haloalkyl, C_1 - C_{12} aminoalkyl, C_1 - C_{12} hydrocarbonoxy, C_2 - C_{12} halohydrocarbonoxy wherein at least two carbon atoms separate the halogen and oxygen atoms;

about 5 to about 60 parts by weight of an acryloyl monomer; and about 20 to about 80 parts by weight of an allylic monomer;

wherein all parts by weight are based on 100 parts by weight resin; and wherein the composition is a powder.

32. (Currently amended) A resin composition, comprising:

about 15 to about 45 parts by weight of a capped poly(arylene ether) produced by capping a poly(arylene ether) consisting essentially of the polymerization product of at least one monohydric phenol having the structure

$$R^1$$
 R^2
 OH
 R^3
 R^4

wherein $\[\]^1$ -R⁴ are each independently hydrogen, halogen, primary or secondary C_1 - C_{12} alkyl, C_2 - C_{12} alkenyl, C_2 - C_{12} alkyl, C_1 - C_{12} aminoalkyl, C_1 - C_{12} hydroxyalkyl, phenyl, C_1 - C_{12} haloalkyl, C_1 - C_{12} aminoalkyl, C_1 - C_{12} hydrocarbonoxy, C_2 - C_{12} halohydrocarbonoxy wherein at least two carbon atoms separate the halogen and oxygen atoms;

about 10 to about 40 parts by weight of a polyfunctional acryloyl monomer; and about 30 to about 70 parts by weight of a polyfunctional allylic monomer;

wherein all parts by weight are based on 100 parts by weight resin; and wherein the composition is a powder.

33. (Original) A resin composition, comprising:

about 25 to about 35 parts by weight of a capped poly(2,6-dimethyl-1,4-phenylene ether);

about 10 to about 20 parts by weight of trimethylolpropane triacrylate or trimethylolpropane trimethacrylate; and

about 50 to about 60 parts by weight of diallyl phthalate;

wherein all parts by weight are based on 100 parts by weight resin; and wherein the composition is a powder.

34. (Currently Amended) A cured resin composition, comprising the reaction product of:

a poly(arylene ether); wherein the poly(arylene ether) is a capped poly(arylene ether) produced by capping a poly(arylene ether) consisting essentially of the polymerization product of at least one monohydric phenol having the structure

$$R^{1}$$
 R^{2}
 R^{2}
 R^{3}
 R^{4}

wherein R^1 - R^4 are each independently hydrogen, halogen, primary or secondary C_1 - C_{12} alkyl, C_2 - C_{12} alkenyl, C_2 - C_{12} alkynyl, C_1 - C_{12} aminoalkyl, C_1 - C_{12} hydroxyalkyl, phenyl, C_1 - C_{12} haloalkyl, C_1 - C_{12} iminoalkyl, C_1 - C_{12} hydroxyalkyl, phenyl, halohydrocarbonoxy wherein at least two carbon atoms separate the halogen and oxygen atoms;

an acryloyl monomer; and

an allylic monomer;

wherein the cured resin composition is the cured product of a curable powder resin composition.

- 35. (Original) The cured resin composition of Claim 34, having a fracture toughness value, K1C, measured according to ASTM D5045 of at least about 0.9 Mpa-m^{1/2}.
 - 36. (Original) An article comprising the composition of Claim 34.

37. (Currently Amended) A method of forming a curable resin composition, comprising:

blending a poly(arylene ether) and an allylic monomer to form a first intimate blend; wherein the poly(arylene ether) is a capped poly(arylene ether) produced by capping a poly(arylene ether) consisting essentially of the polymerization product of at least one monohydric phenol having the structure

$$R^{2}$$
 R^{2}
 R^{2}
 R^{2}
 R^{4}

wherein R¹-R⁴ are each independently hydrogen, halogen, primary or secondary C₁-C₁₂ alkyl, C₂-C₁₂ alkynyl, C₁-C₁₂ aminoalkyl, C₁-C₁₂ hydroxyalkyl, phenyl, C₁-C₁₂ haloalkyl, C₁-C₁₂ aminoalkyl, C₁-C₁₂ hydrocarbonoxy, C₂-C₁₂ halohydrocarbonoxy wherein at least two carbon atoms separate the halogen and oxygen atoms;

blending the first intimate blend and an acryloyl monomer to form a second intimate blend; and

processing the second intimate blend to form a curable powder.

- 38. (Original) The method of Claim 37, wherein processing the second intimate blend to form a curable powder comprises grinding at a temperature less than about -75°C.
- 39. (Original) The method of Claim 37, further comprising blending the curable powder with a curing catalyst.

40. (Currently Amended) A method of preparing a curable composition, comprising:

blending about 20 to about 80 parts by weight of an allylic monomer with about 10 to about 50 parts by weight of a poly(arylene ether) to form a first intimate blend; wherein the poly(arylene ether) is a capped poly(arylene ether) produced by capping a poly(arylene ether) consisting essentially of the polymerization product of at least one monohydric phenol having the structure

$$R^1$$
 R^2
 OH
 R^3
 R^4

wherein R¹-R⁴ are each independently hydrogen, halogen, primary or secondary C₁-C₁₂ alkyl, C₂-C₁₂ alkenyl, C₂-C₁₂ alkynyl, C₁-C₁₂ aminoalkyl, C₁-C₁₂ hydroxyalkyl, phenyl, C₁-C₁₂ haloalkyl, C₁-C₁₂ iminoalkyl, C₁-C₁₂ hydrocarbonoxy, C₂-C₁₂ halohydrocarbonoxy wherein at least two carbon atoms separate the halogen and oxygen atoms;

blending the first intimate blend with about 5 to about 60 parts by weight of an acryloyl monomer to form a second intimate blend;

grinding the second intimate blend at a temperature less than about -75°C to form a first curable powder; and

blending the first powder with a curing catalyst to form a second curable powder; wherein all parts by weight are based on 100 parts by weight resin.